

LAMPIRAN

Lampiran 1. ASTM D 4644-08

Standard Test Method for Slake Durability of Shales and Similar Weak Rocks¹

This standard is issued under the fixed designation D4644; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon (^ε) indicates an editorial change since the last revision or reappraisal.

1. Scope*

1.1 This test method covers the determination of the slake durability index of a shale or other similar rock after two drying and wetting cycles with abrasion.

1.2 All observed and calculated values shall conform to the guidelines for significant digits and rounding established in Practice **D6026**.

1.2.1 The method used to specify how data are collected, calculated, or recorded in this standard is not directly related to the accuracy to which the data can be applied in design or other uses, or both. How one applies the results obtained using this standard is beyond its scope.

1.3 The values stated in SI units are to be regarded as standard. The values given in parentheses are mathematical conversions to inch-pound units that are provided for information only and are not considered standard.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*²

D653 Terminology Relating to Soil, Rock, and Contained Fluids

D2113 Practice for Rock Core Drilling and Sampling of Rock for Site Investigation

D2216 Test Methods for Laboratory Determination of Water (Moisture) Content of Soil and Rock by Mass

D3740 Practice for Minimum Requirements for Agencies Engaged in Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction

D5079 Practices for Preserving and Transporting Rock Core Samples

D6026 Practice for Using Significant Digits in Geotechnical Data

E11 Specification for Woven Wire Test Sieve Cloth and Test Sieves

3. Terminology

3.1 For terminology used in this test method, refer to Terminology **D653**

3.2 *Definitions of Terms Specific to This Standard:*

3.2.1 *slake durability index*—the percentage by dry mass of a collection of shale pieces retained on a 2.00 mm (No. 10) sieve after two cycles of oven drying and 10 min of soaking in water with a standard tumbling and abrasion action.

4. Significance and Use

4.1 The test method is used to estimate qualitatively the durability of weak rocks in the service environment. **(1-7)**,³

4.2 This test method is used to assign quantitative durability values to weak rocks. A primary example is the Franklin Rating System **(1)**.

NOTE 1—The quality of the result produced by this standard is dependent on the competence of the personnel performing it, and the suitability of the equipment and facilities used. Agencies that meet the criteria of Practice **D3740** are generally considered capable of competent and objective testing, sampling, inspection, and so forth. Users of this standard are cautioned that compliance with Practice **D3740** does not in itself assure reliable results. Reliable results depend on many factors; Practice **D3740** provides a means of evaluating some of those factors.

5. Apparatus

5.1 *Slake Durability Device*—The drum (Fig. 1) shall be made of 2.00 mm (No. 10) square-mesh, woven-wire cloth, conforming to the requirements of Specification **E11**. It shall be cylindrical in shape, with a diameter of 140 mm (5.5 in.) and a length of 100 mm (3.9 in.). The ends shall be rigid plates, with one removable end. It must be sufficiently strong to retain its shape during use, but neither the exterior of the mesh nor the interior of the drum shall be obstructed by a support. The drum shall be able to withstand a temperature of 110 ± 5°C (230 ± 6

¹ This test method is under the jurisdiction of ASTM Committee **D18** on Soil and Rock and is the direct responsibility of Subcommittee **D18.12** on Rock Mechanics.

Current edition approved July 1, 2008. Published July 2008. Originally approved in 1987. Last previous edition approved in 2004 as D4644 – 04. DOI: 10.1520/D4644-08.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For Annual Book of ASTM Standards volume information, refer to the standard's Document Summary page on the ASTM website.

³ The boldface numbers in parentheses refer to the list of references at the end of this standard.



D4644 - 08




FIG. 1 Critical Dimensions of Slake Durability Device Showing Critical Dimensions

9°F). A trough shall support the drum in a horizontal manner such that the drum is free to rotate about its axis. The trough shall be capable of being filled with slaking fluid to 20 mm (0.8 in.) below the drum axis, and shall allow at least 40 mm (1.6 in.) unobstructed clearance between the trough and the bottom of the mesh. The drum shall be rotated by a motor capable of maintaining a speed of 20 rpm, constant to within 5 %, for a period of 10 min. Devices conforming to these requirements are commercially available.

5.2 *Drying Oven*, thermostatically controlled, capable of maintaining a temperature of 110 ± 5°C (230 ± 9°F).

5.3 *Balance*, sensitive to 1 g and having a 2000-g capacity.

5.4 *Miscellaneous Apparatus*, including a brush and hammer.

5.5 *Distilled Water*.

6. Test Sample and Specimen

6.1 Collect, transport, and store test samples and test specimens in such a manner as to retain the natural water content using the guidelines in Practices D2113 and D5079 and Test Method D2216.

6.2 The test specimen shall consist of ten representative, intact, roughly equidimensional shale fragments weighing 40 g to 60 g each. These fragments may be naturally occurring or may be produced by breaking with a hammer. Such fragments may be obtained from rock cores or from test pits, and their sizes will vary with the method of sampling. Break off any sharp corners, if possible, and remove any dust by brushing the fragment just prior to weighing. The total test specimen shall weigh 450 to 550 g.

7. Procedure

7.1 Photograph specimen prior to placement in drum.

7.2 *Water Content*—Using Test Method D2216, determine the water content of each test specimen before testing. This shall be done with the shale fragments in the drum to be used for the actual testing.

7.3 Mount the drum in the trough and couple to the motor. Fill the trough with distilled water at room temperature to 20 mm (0.8 in.) below the drum axis. Rotate the drum at 20 rpm

for a period of 10 min. Record the water temperature at the beginning and end of the run.

7.4 Remove the drum from the trough immediately after the rotation period is complete and dry the drum and the specimen retained in the oven the same as in 7.2 and obtain the oven-dried mass.

7.5 Repeat 7.3 and 7.4 to obtain a final oven-dried mass for the second cycle.

7.6 Photograph specimen retained and file a copy of the photo with the laboratory report, or record standard verbal descriptions, as follows:

7.6.1 *Type I*—Retained specimen remain virtually unchanged.

7.6.2 *Type II*—Retained specimen consist of large and small fragments.

7.6.3 *Type III*—Retained specimen is exclusively small fragments.

7.7 See Fig. 2 for representative photographs of the three types.

8. Calculations

8.1 Calculate the slake durability index (second cycle), as follows:

$$I_d(2) = \frac{W_F - B}{C} \times 100 \quad (1)$$

where:

$I_d(2)$ = slake durability index (second cycle),

B = mass of drum plus oven-dried specimen before the first cycle, g,

W_F = mass of drum plus oven-dried specimen retained after the second cycle, g, and

C = mass of drum, g.

9. Report

9.1 The report shall include the following:

9.1.1 Description of the specimen and where it was obtained.

9.1.2 Slake durability index (second cycle) to the nearest 0.1 %.

9.1.3 Range and average value of the water temperature.

9.1.4 Natural water content.



D4644 – 08



FIG. 2 Illustration of Fragment Types Retained

9.1.5 Description of the appearance of the fragments retained in the drum (see 7.6).

10. Precision and Bias

10.1 Test data on precision is not presented due to the nature of shale and other similar rock tested by this test method. It is either not feasible or too costly at this time to produce multiple specimens which have uniform physical properties. Any variation observed on the data is just as likely to be due to specimen

variation as to operator or laboratory testing variation: Subcommittee D18.12 welcomes proposals that would allow for development of a valid precision statement. There is no accepted reference value of shale or weak rock for this test method; therefore, bias cannot be determined.

11. Keywords

11.1 abrasion resistance; shale; slake durability; weak rocks



REFERENCES

- (1) Franklin Trow Associates, “Field Evaluation of Shales for Construction Projects,” Research and Development Project No. 1404, Ministry of Transportation and Communications, Research and Development Branch, Downsview, Ontario, March 1979.
- (2) Chapman, D. R., “Shale Classification Tests and Systems: A Comparative Study,” *MSCE Thesis and Joint Highway Research Project No. 75-11*, Purdue University, West Lafayette, IN, June 1975, 90 pp.
- (3) Deo, P., “Shales as Embankment Materials,” *Ph.D. Thesis and Joint Highway Research Project No. 45*, Purdue University, West Lafayette, IN, December 1972, 202 pp.
- (4) International Society for Rock Mechanics, “Suggested Methods for Determining Slake-Durability Index Properties,” *Commission on Standardization of Laboratory and Field Tests*, November 1972.
- (5) Lutton, R. J., “Design and Construction of Compacted Shale Embankments, Volume 3, Slaking Indexes for Design,” *Report No. FHWA-RD-77-1*, Federal Highway Administration, Washington, DC, February 1977.
- (6) Surendra, M., “Additives to Control Slaking in Compacted Shales,” *Ph.D. Thesis and Joint Highway Research Project No. 80-6*, Purdue University, West Lafayette, IN, May 1980, 277 pp.
- (7) Oakland, M. W., and Lovell, C. W., “Classification and Other Standard Tests for Shale Embankment,” *Joint Highway Research Project No. 82-4*, Purdue University, West Lafayette, IN, February 1982, 171 pp.

SUMMARY OF CHANGES

Committee D18 has identified the location of selected changes to this standard since the last issue (D4644 – 04) that may impact the use of this standard. (Approved July 1, 2008.)

- (1) Edited Sections 1.3 and 3.2.1.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the ASTM website (www.astm.org/COPYRIGHT).


Lampiran 2. Hasil Uji Pematatan

Tabel 1. Hasil Uji Pematatan

Air	ml	400	450	500	550	600	650		
W ₁	g	1746.00	1745.00	1810.00	1810.00	1745.00	1745.00		
W ₂	g	3493.00	3599.00	3739.00	3729.00	3605.00	3558.00		
W _m	g	1747.00	1854.00	1929.00	1919.00	1860.00	1813.00		
D	cm	10.00	10.00	10.11	10.11	10.00	10.00		
h	cm	12.06	12.06	12.03	12.03	12.06	12.06		
V	cm ³	947.16	947.16	965.71	965.71	947.16	947.16		
γ	kN/m ³	18.09	19.20	19.60	19.49	19.26	18.78		
		I	II	III	I	II	III	I	II
No Cawan		R6	Z9	E2	K3	D9	F2	D7	L6
		9.13	9.15	9.38	9.13	8.66	9.67	10.25	8.69
W ₀	g	29.13	29.15	29.38	29.13	28.66	29.67	30.25	28.69
W _b	g	26.52	26.49	26.76	26.05	25.69	26.66	26.90	25.38
W _d	g	2.61	2.66	2.62	3.08	2.97	3.01	3.35	3.31
W _w = W _b - W _d	g	17.39	17.34	17.38	16.92	17.03	16.99	16.65	16.69
W _s = W _d - W ₀	g	15.0	15.3	15.1	18.2	17.4	17.7	20.1	19.8
w	%	15.1	15.3	15.1	18.2	17.4	17.7	20.1	19.8
w rata-rata	%	15.1	15.1	15.1	17.8	17.8	17.8	20.0	20.0
γ _d	kN/m ³	15.71	15.71	15.71	16.30	16.30	16.30	16.33	16.33
G _s		2.70	2.70	2.70	2.70	2.70	2.70	2.70	2.70
γ _{av}	kN/m ³	18.55	18.55	18.55	17.67	17.67	17.67	16.99	16.99
		I	II	III	I	II	III	I	II
		R6	Z9	E2	K3	D9	F2	D7	L6
		9.13	9.15	9.38	9.13	8.66	9.67	10.25	8.69
		29.13	29.15	29.38	29.13	28.66	29.67	30.25	28.69
		26.52	26.49	26.76	26.05	25.69	26.66	26.90	25.38
		2.61	2.66	2.62	3.08	2.97	3.01	3.35	3.31
		17.39	17.34	17.38	16.92	17.03	16.99	16.65	16.69
		15.0	15.3	15.1	18.2	17.4	17.7	20.1	19.8
		15.1	15.3	15.1	18.2	17.4	17.7	20.1	19.8
		15.71	15.71	15.71	16.30	16.30	16.30	16.33	16.33
		2.70	2.70	2.70	2.70	2.70	2.70	2.70	2.70
		18.55	18.55	18.55	17.67	17.67	17.67	16.99	16.99
		I	II	III	I	II	III	I	II
		R6	Z9	E2	K3	D9	F2	D7	L6
		9.13	9.15	9.38	9.13	8.66	9.67	10.25	8.69
		29.13	29.15	29.38	29.13	28.66	29.67	30.25	28.69
		26.52	26.49	26.76	26.05	25.69	26.66	26.90	25.38
		2.61	2.66	2.62	3.08	2.97	3.01	3.35	3.31
		17.39	17.34	17.38	16.92	17.03	16.99	16.65	16.69
		15.0	15.3	15.1	18.2	17.4	17.7	20.1	19.8
		15.1	15.3	15.1	18.2	17.4	17.7	20.1	19.8
		15.71	15.71	15.71	16.30	16.30	16.30	16.33	16.33
		2.70	2.70	2.70	2.70	2.70	2.70	2.70	2.70
		18.55	18.55	18.55	17.67	17.67	17.67	16.99	16.99
		I	II	III	I	II	III	I	II
		R6	Z9	E2	K3	D9	F2	D7	L6
		9.13	9.15	9.38	9.13	8.66	9.67	10.25	8.69
		29.13	29.15	29.38	29.13	28.66	29.67	30.25	28.69
		26.52	26.49	26.76	26.05	25.69	26.66	26.90	25.38
		2.61	2.66	2.62	3.08	2.97	3.01	3.35	3.31
		17.39	17.34	17.38	16.92	17.03	16.99	16.65	16.69
		15.0	15.3	15.1	18.2	17.4	17.7	20.1	19.8
		15.1	15.3	15.1	18.2	17.4	17.7	20.1	19.8
		15.71	15.71	15.71	16.30	16.30	16.30	16.33	16.33
		2.70	2.70	2.70	2.70	2.70	2.70	2.70	2.70
		18.55	18.55	18.55	17.67	17.67	17.67	16.99	16.99
		I	II	III	I	II	III	I	II
		R6	Z9	E2	K3	D9	F2	D7	L6
		9.13	9.15	9.38	9.13	8.66	9.67	10.25	8.69
		29.13	29.15	29.38	29.13	28.66	29.67	30.25	28.69
		26.52	26.49	26.76	26.05	25.69	26.66	26.90	25.38
		2.61	2.66	2.62	3.08	2.97	3.01	3.35	3.31
		17.39	17.34	17.38	16.92	17.03	16.99	16.65	16.69
		15.0	15.3	15.1	18.2	17.4	17.7	20.1	19.8
		15.1	15.3	15.1	18.2	17.4	17.7	20.1	19.8
		15.71	15.71	15.71	16.30	16.30	16.30	16.33	16.33
		2.70	2.70	2.70	2.70	2.70	2.70	2.70	2.70
		18.55	18.55	18.55	17.67	17.67	17.67	16.99	16.99
		I	II	III	I	II	III	I	II
		R6	Z9	E2	K3	D9	F2	D7	L6
		9.13	9.15	9.38	9.13	8.66	9.67	10.25	8.69
		29.13	29.15	29.38	29.13	28.66	29.67	30.25	28.69
		26.52	26.49	26.76	26.05	25.69	26.66	26.90	25.38
		2.61	2.66	2.62	3.08	2.97	3.01	3.35	3.31
		17.39	17.34	17.38	16.92	17.03	16.99	16.65	16.69
		15.0	15.3	15.1	18.2	17.4	17.7	20.1	19.8
		15.1	15.3	15.1	18.2	17.4	17.7	20.1	19.8
		15.71	15.71	15.71	16.30	16.30	16.30	16.33	16.33
		2.70	2.70	2.70	2.70	2.70	2.70	2.70	2.70
		18.55	18.55	18.55	17.67	17.67	17.67	16.99	16.99
		I	II	III	I	II	III	I	II
		R6	Z9	E2	K3	D9	F2	D7	L6
		9.13	9.15	9.38	9.13	8.66	9.67	10.25	8.69
		29.13	29.15	29.38	29.13	28.66	29.67	30.25	28.69
		26.52	26.49	26.76	26.05	25.69	26.66	26.90	25.38
		2.61	2.66	2.62	3.08	2.97	3.01	3.35	3.31
		17.39	17.34	17.38	16.92	17.03	16.99	16.65	16.69
		15.0	15.3	15.1	18.2	17.4	17.7	20.1	19.8
		15.1	15.3	15.1	18.2	17.4	17.7	20.1	19.8
		15.71	15.71	15.71	16.30	16.30	16.30	16.33	16.33
		2.70	2.70	2.70	2.70	2.70	2.70	2.70	2.70
		18.55	18.55	18.55	17.67	17.67	17.67	16.99	16.99
		I	II	III	I	II	III	I	II
		R6	Z9	E2	K3	D9	F2	D7	L6
		9.13	9.15	9.38	9.13	8.66	9.67	10.25	8.69
		29.13	29.15	29.38	29.13	28.66	29.67	30.25	28.69
		26.52	26.49	26.76	26.05	25.69	26.66	26.90	25.38
		2.61	2.66	2.62	3.08	2.97	3.01	3.35	3.31
		17.39	17.34	17.38	16.92	17.03	16.99	16.65	16.69
		15.0	15.3	15.1	18.2	17.4	17.7	20.1	19.8
		15.1	15.3	15.1	18.2	17.4	17.7	20.1	19.8
		15.71	15.71	15.71	16.30	16.30	16.30	16.33	16.33
		2.70	2.70	2.70	2.70	2.70	2.70	2.70	2.70
		18.55	18.55	18.55	17.67	17.67	17.67	16.99	16.99
		I	II	III	I	II	III	I	II
		R6	Z9	E2	K3	D9	F2	D7	L6
		9.13	9.15	9.38	9.13	8.66	9.67	10.25	8.69
		29.13	29.15	29.38	29.13	28.66	29.67	30.25	28.69
		26.52	26.49	26.76	26.05	25.69	26.66	26.90	25.38
		2.61	2.66	2.62	3.08	2.97	3.01	3.35	3.31
		17.39	17.34	17.38	16.92	17.03	16.99	16.65	16.69
		15.0	15.3	15.1	18.2	17.4	17.7	20.1	19.8
		15.1	15.3	15.1	18.2	17.4	17.7	20.1	19.8
		15.71	15.71	15.71	16.30	16.30	16.30	16.33	16.33
		2.70	2.70	2.70	2.70	2.70	2.70	2.70	2.70
		18.55	18.55	18.55	17.67	17.67	17.67	16.99	16.99
		I	II	III	I	II	III	I	II
		R6	Z9	E2	K3	D9	F2	D7	L6
		9.13	9.15	9.38	9.13	8.66	9.67	10.25	8.69
		29.13	29.15	29.38	29.13	28.66	29.67	30.25	28.69
		26.52	26.49	26.76	26.05	25.69	26.66	26.90	25.38
		2.61	2.66	2.62	3.08	2.97	3.01	3.35	3.31
		17.39	17.34	17.38	16.92	17.03	16.99	16.65	16.69
		15.0	15.3	15.1	18.2	17.4	17.7	20.1	19.8
		15.1	15.3	15.1	18.2				

Keterangan:

- W_1 : Berat silinder kosong
 W_2 : Berat silinder + tanah padat
 W_m : Berat tanah padat
 D : Diameter silinder
 H : Tinggi silinder
 V : Volume silinder
 γ : Berat volume basah
 W_o : Berat cawan kosong
 W_b : Berat cawan + tanah basah
 W_d : Berat cawan + tanah kering
 W_w : Berat air
 W_s : Berat tanah kering
 w : Kadar air
 w rata-rata : Kadar air rata-rata
 γ_d : Berat volume kering
 G_s : Berat jenis
 γ_{zav} : Berat volume *zero air void*



Gambar 1. Grafik Uji Pemadatan Standar


Lampiran 3. Hasil Pengujian dan Grafik Batas Cair

Tabel 1. Hasil Pengujian Batas Cair

Percobaan ke-	1		2		3		4		5	
Jumlah pukulan	34	31	28	27	24	23	17	18	14	13
Nomor cawan	17	N9	J2	D4	C7	S6	D1	J9	A5	K2
W_1	9.14	9.32	10.41	9.34	9.13	9.77	9.24	9.77	9.26	9.38
W_2	29.14	29.32	30.41	29.34	29.13	29.77	29.24	29.77	29.26	29.38
W_3	22.67	22.41	22.93	21.88	21.63	22.18	21.55	22.08	21.33	21.14
$W_w = W_2 - W_3$	6.47	6.91	7.48	7.46	7.5	7.59	7.69	7.69	7.93	8.24
$W_s = W_3 - W_1$	13.53	13.09	12.52	12.54	12.5	12.41	12.31	12.31	12.07	11.76
$w = (W_w/W_s)$	47.82	52.79	59.74	59.49	60.00	61.16	62.47	62.47	65.70	70.07
Rata-rata W	50.30		59.62		60.58		62.47		67.88	

Keterangan:

- W_1 : Berat cawan kosong (g)
 W_2 : Berat cawan + tanah basah (g)
 W_3 : Berat cawan + tanah kering (g)
 W_w : Berat air
 W_s : Berat tanah kering
 w : Kadar air



Gambar 1. Grafik Batas Cair

Lampiran 4. Hasil Pengujian dan Grafik Distribusi Ukuran Butir

Tabel 1. Hasil Uji Saringan


Berat spesimen kering oven : 52.87 g				
Nomor Saringan	Ukuran butir (mm)	Berat tertahan (g)	Persen berat tertahan (g)	Persen lolos saringan (%)
#4	4.740	0.00	0.00	100.0
#10	2.000	0.00	0.00	100.0
#20	0.850	1.45	2.74	97.3
#40	0.425	1.46	2.76	94.5
#60	0.250	0.31	0.59	93.9
#140	0.105	0.14	0.26	93.6
#200	0.075	0.10	0.19	93.5
Pan	< 0,075	49.41	93.46	0.0

Tabel 2. Hasil Uji Hidrometer

t (menit)	Pembacaan skala hidrometer		T °C	R ¹	L (cm)	K	D (mm)	R	P (%)	PA (%)
	R ₁	R ₂								
2	14.0	0	28.60	15.00	12.06	0.012356	0.03034	17.75	0.34	0.31
5	11.0	0	28.60	12.00	12.47	0.012356	0.01952	14.75	0.28	0.26
30	6.0	0	28.80	7.00	13.17	0.0123664	0.00819	9.90	0.19	0.17
60	5.0	0	29.10	6.00	13.31	0.012458	0.00587	9.13	0.17	0.16
250	4.0	0	28.50	5.00	13.44	0.0124675	0.00289	7.68	0.15	0.14
1440	1.0	0	28.20	2.00	13.86	0.0129264	0.00127	4.45	0.08	0.08

Keterangan:

- t : Waktu pembacaan
R₁ : Pembacaan hidrometer larutan tanah
R₂ : Pembacaan hidrometer larutan reagen
T : Temperatur
R¹ : Skala hidrometer terkalibrasi meniskus
L : Kedalaman
K : Konstanta
D : Diameter butiran
R : Skala hidrometer terkalibrasi
P : Persen berat
PA : *Adjust percent*



Gambar 1. Kurva Distribusi Ukuran Butir

Lampiran 5. Hasil Pengujian *Slake Durability*

Tabel 1 Hasil pengujian spesimen A 0%

Drum Kiri			Drum Kanan		
Siklus	Berat spesimen (g)	Berat endapan (g)	Siklus	Berat spesimen (g)	Berat endapan (g)
0	567		0	564	
1	3.140	563.860	1	5.560	558.440
2	0.850	2.290	2	0.670	4.890
3	0.620	0.230	3	0.470	0.200
4	0.500	0.500	4	0.390	0.080
5	0.000	0.500	5	0.000	0.390

Tabel 2 Hasil pengujian spesimen B 0 %

Drum Kiri			Drum Kanan		
Siklus	Berat spesimen (g)	Berat endapan (g)	Siklus	Berat spesimen (g)	Berat endapan (g)
0	482		0	484	
1	9.000	473.000	1	8.000	476.000
2	7.000	2.000	2	6.000	2.000
3	4.190	2.810	3	3.450	2.550
4	3.800	3.800	4	3.000	0.450
5	3.000	0.800	5	2.500	0.500

Tabel 3 Hasil pengujian spesimen A 10 % *dry mix*

Drum Kiri			Drum Kanan		
Siklus	Berat spesimen (g)	Berat endapan (g)	Siklus	Berat spesimen (g)	Berat endapan (g)
0	535.52		0	450	
1	133.520	402.000	1	74.900	374.100
2	99.520	34.000	2	55.330	19.570
3	83.930	15.590	3	44.130	11.200
4	72.100	11.830	4	35.050	9.080
5	60.520	11.580	5	29.470	5.580

Tabel 4 Hasil pengujian spesimen B 10 % *dry mix*

Drum Kiri			Drum Kanan		
Siklus	Berat spesimen (g)	Berat endapan (g)	Siklus	Berat spesimen (g)	Berat endapan (g)
0	450		0	449	
1	417.000	33.000	1	423.000	26.000
2	362.000	55.000	2	374.000	49.000
3	319.000	43.000	3	323.000	51.000
4	278.000	41.000	4	300.000	23.000
5	245.000	33.000	5	270.000	30.000

Tabel 5 Hasil pengujian spesimen A 10 % *spray mix*

Drum Kiri			Drum Kanan		
Siklus	Berat spesimen (g)	Berat endapan (g)	Siklus	Berat spesimen (g)	Berat endapan (g)
0	540		0	542.27	
1	155.020	384.980	1	165.460	376.810
2	96.050	58.970	2	97.630	67.830
3	58.600	37.450	3	59.440	38.190
4	46.440	12.160	4	46.370	13.070
5	38.150	8.290	5	37.150	9.220

Tabel 6. Hasil pengujian spesimen B 10 % *spray mix*

Drum Kiri			Drum Kanan		
Siklus	Berat spesimen (g)	Berat endapan (g)	Siklus	Berat spesimen (g)	Berat endapan (g)
0	497.81		0	497.1	
1	384.810	113.000	1	407.100	90.000
2	263.810	121.000	2	282.100	125.000
3	186.530	77.280	3	191.030	91.070
4	149.850	36.680	4	151.730	39.300
5	122.190	27.660	5	29.670	122.060