

Miniature Circuit Breaker (MCB) Domae



Domae Miniature Circuit Breaker (MCB)

Untuk pemakaian dengan arus hubung singkat $\leq 4,5$ kA

- Kapasitas pemutusan:
Standar SNI 04-6507.1-2002/Amd1-2006 (IEC 60898-1),
Icn = 4500A (230V - 1P, 400V - 3P).
- Kurva C (magnetis trip antara 5 dan 10 In).




MCB Domae
1 Kutub



MCB Domae
2 Kutub



MCB Domae
3 Kutub



Jumlah Kutub	Pengenal (A)	Referensi	Harga (Rp)	SS	
1 Kutub	2	DOM12251SNI	68,750	1	
	4	DOM12252SNI	68,750	1	
	6	DOM11340SNI	59,400	1	
	10	DOM11341SNI	59,400	1	
	16	DOM11342SNI	59,400	1	
	20	DOM11343SNI	59,400	1	
	25	DOM11344SNI	67,100	1	
	32	DOM11345SNI	69,300	1	
	40	DOM11346SNI	79,750	1	
	50	DOM11335SNI	179,300	1	
	63	DOM11336SNI	179,300	1	
	2 Kutub	2	DOM11228SNI	205,150	1
		4	DOM11229SNI	205,150	1
6		DOM11230SNI	169,950	1	
10		DOM11231SNI	169,950	1	
16		DOM11232SNI	169,950	1	
20		DOM11233SNI	169,950	1	
25		DOM11234SNI	196,350	1	
32		DOM11235SNI	203,500	1	
40		DOM11236SNI	203,500	1	
50		DOM11237SNI	381,150	1	
63		DOM11238SNI	381,150	1	
3 Kutub		6	DOM11347SNI	279,950	1
		10	DOM11348SNI	279,950	1
	16	DOM11349SNI	279,950	1	
	20	DOM11350SNI	279,950	1	
	25	DOM11351SNI	296,450	1	
	32	DOM11352SNI	325,600	1	
	40	DOM11353SNI	335,500	1	
	50	DOM11337SNI	635,250	1	
	63	DOM11338SNI	635,250	1	

EasyPact EZC

Moulded Case Circuit Breaker 100A 3P/4P

PTCCB

EasyPact EZC100 B/F/N/H dengan 3P/4P

- Aplikasi untuk instalasi listrik dengan kapasitas pemutusan rendah.
- Kapasitas Pemutusan : 7.5 kA s/d 30 kA pada 380/415 VAC.
- Thermal magnetic trip unit, tidak dapat disetel (*non adjustable*).
- Fixed type, front connection.
- Satu ukuran (*frame size*) untuk semua rating.
- Memenuhi standar IEC 60947-2.
- Rated @ 125V DC (1P) dan @ 250V DC (2P in series)



EZC100, 3P



EZC100, 4P

EasyPact	Ir (A)	3P	Harga (Rp)	SS	4P	Harga (Rp)	SS
EasyPact EZC100B (7.5 kA)							
EZC100B	15	EZC100B3015	568,700	1			
EZC100B	20	EZC100B3020	568,700	1			
EZC100B	25	EZC100B3025	568,700	1			
EZC100B	30	EZC100B3030	568,700	1			
EZC100B	40	EZC100B3040	568,700	1			
EZC100B	50	EZC100B3050	568,700	1			
EZC100B	60	EZC100B3060	619,850	1			
EasyPact EZC100F (10 kA)							
EZC100F	15	EZC100F3015	607,200	1			
EZC100F	20	EZC100F3020	607,200	1			
EZC100F	25	EZC100F3025	607,200	1			
EZC100F	30	EZC100F3030	607,200	1			
EZC100F	40	EZC100F3040	607,200	1			
EZC100F	50	EZC100F3050	607,200	1			
EZC100F	60	EZC100F3060	671,550	1			
EZC100F	75	EZC100F3075	671,550	1			
EZC100F	80	EZC100F3080	671,550	1			
EZC100F	100	EZC100F3100	671,550	1			
EasyPact EZC100N (18 kA @ 380V / 15 kA @ 400/415V)							
EZC100N	15	EZC100N3015	751,850	1	EZC100N4015	1,271,600	2
EZC100N	20	EZC100N3020	751,850	1	EZC100N4020	1,271,600	2
EZC100N	25	EZC100N3025	751,850	1	EZC100N4025	1,271,600	2
EZC100N	30	EZC100N3030	751,850	1	EZC100N4030	1,271,600	2
EZC100N	40	EZC100N3040	751,850	1	EZC100N4040	1,271,600	2
EZC100N	50	EZC100N3050	751,850	1	EZC100N4050	1,271,600	2
EZC100N	60	EZC100N3060	821,700	1	EZC100N4060	1,388,200	2
EZC100N	75	EZC100N3075	821,700	1	EZC100N4075	1,388,200	2
EZC100N	80	EZC100N3080	821,700	1	EZC100N4080	1,388,200	2
EZC100N	100	EZC100N3100	821,700	1	EZC100N4100	1,388,200	2
EasyPact EZC100H (30 kA)							
EZC100H	15	EZC100H3015	876,700	1	EZC100H4015	1,332,100	2
EZC100H	20	EZC100H3020	876,700	1	EZC100H4020	1,332,100	2
EZC100H	25	EZC100H3025	876,700	1	EZC100H4025	1,332,100	2
EZC100H	30	EZC100H3030	876,700	1	EZC100H4030	1,332,100	2
EZC100H	40	EZC100H3040	876,700	1	EZC100H4040	1,332,100	2
EZC100H	50	EZC100H3050	876,700	1	EZC100H4050	1,332,100	2
EZC100H	60	EZC100H3060	963,050	1	EZC100H4060	1,504,800	2
EZC100H	75	EZC100H3075	963,050	1	EZC100H4075	1,504,800	2
EZC100H	80	EZC100H3080	963,050	1	EZC100H4080	1,504,800	2
EZC100H	100	EZC100H3100	963,050	1	EZC100H4100	1,504,800	2

EasyPact Ezc

Moulded Case Circuit Breaker 250A 3P/4P

PTCCB

EasyPact Ezc250 F/N/H

- Aplikasi untuk instalasi listrik dengan kapasitas pemutusan rendah.
- Kapasitas Pemutusan : 18 kA s/d 36 kA pada 380/415 VAC .
- Thermal magnetic trip unit, tidak dapat disetel (*non adjustable*).
- Fixed type, front connection,
- Satu ukuran (*frame size*) untuk semua rating.
- Memenuhi standar IEC 60947-2.
- Rated @ 125V DC (1P) dan @ 250V DC (2P in series)



Ezc250, 3P

EasyPact	Ir (A)	2P	Harga (Rp)	SS	3P	Harga (Rp)	SS
EasyPact Ezc250F (18 kA)							
Ezc250F	100				Ezc250F3100	1,313,400	1
Ezc250F	125				Ezc250F3125	1,344,200	1
Ezc250F	160				Ezc250F3160	1,381,600	1
Ezc250F	200				Ezc250F3200	1,454,200	1
Ezc250F	225				Ezc250F3225	1,454,200	1
Ezc250F	250				Ezc250F3250	1,454,200	1
EasyPact Ezc250N (25 kA)							
Ezc250N	100				Ezc250N3100	1,399,200	1
Ezc250N	125				Ezc250N3125	1,465,200	1
Ezc250N	160				Ezc250N3160	1,527,900	1
Ezc250N	200				Ezc250N3200	1,817,200	1
Ezc250N	225				Ezc250N3225	1,817,200	1
Ezc250N	250				Ezc250N3250	1,817,200	1
EasyPact Ezc250H (36 kA)							
Ezc250H	100	Ezc250H2100	1,741,300	2	Ezc250H3100	1,624,700	1
Ezc250H	125	Ezc250H2125	1,741,300	2	Ezc250H3125	1,675,300	1
Ezc250H	160	Ezc250H2160	1,818,300	2	Ezc250H3160	1,817,200	1
Ezc250H	200	Ezc250H2200	2,132,900	2	Ezc250H3200	1,889,800	1
Ezc250H	225	Ezc250H2225	2,132,900	2	Ezc250H3225	1,889,800	1
Ezc250H	250	Ezc250H2250	2,132,900	2	Ezc250H3250	1,889,800	1



Ezc250, 4P

EasyPact	Ir (A)	4P	Harga (Rp)	SS
EasyPact Ezc250N (25 kA)				
Ezc250N	100	Ezc250N4100	1,925,000	2
Ezc250N	125	Ezc250N4125	2,011,900	2
Ezc250N	160	Ezc250N4160	2,090,000	2
Ezc250N	200	Ezc250N4200	2,255,000	2
Ezc250N	225	Ezc250N4225	2,255,000	2
Ezc250N	250	Ezc250N4250	2,255,000	2
EasyPact Ezc250H (36 kA)				
Ezc250H	100	Ezc250H4100	2,261,600	2
Ezc250H	125	Ezc250H4125	2,261,600	2
Ezc250H	160	Ezc250H4160	2,512,400	2
Ezc250H	200	Ezc250H4200	2,621,300	2
Ezc250H	225	Ezc250H4225	2,621,300	2
Ezc250H	250	Ezc250H4250	2,621,300	2

EasyPact EZC

Moulded Case Circuit Breaker 250 A Dengan ELCB dan 400-630A

PTCCB

EasyPact EZCV250 N/H

- Aplikasi untuk instalasi listrik dengan kapasitas pemutusan rendah.
- Kapasitas Pemutusan : 25 kA s/d 36 kA pada 380/415 VAC.
- Thermal magnetic trip unit, tidak dapat disetel (*non adjustable*).
- Integrated dengan proteksi arus bocor (*Earth Leakage Protection*).
- Fixed type, front connection.
- Satu ukuran (*frame size*) dengan EZC250.
- Memenuhi standar IEC 60947-2.
- Rated @ 125V DC (1P) dan @ 250V DC (2P in series)



EZCV250, 3P



EZCV250, 4P

EasyPact	Ir (A)	3P	Harga (Rp)	SS	4P	Harga (Rp)	SS
EasyPact EZC250N (25 kA)							
EZC250N	100	EZCV250N3100	3,566,200	2	EZCV250N4100	4,992,900	2
EZC250N	125	EZCV250N3125	4,064,500	2	EZCV250N4125	5,691,400	2
EZC250N	160	EZCV250N3160	4,552,900	2	EZCV250N4160	6,204,000	2
EZC250N	200	EZCV250N3200	4,687,100	2	EZCV250N4200	6,560,400	2
EZC250N	225	EZCV250N3225	4,687,100	2	EZCV250N4225	6,560,400	2
EZC250N	250	EZCV250N3250	4,687,100	2	EZCV250N4250	6,560,400	2
EasyPact EZC250H (36 kA)							
EZC250H	100	EZCV250H3100	4,467,100	2	EZCV250H4100	5,194,200	2
EZC250H	125	EZCV250H3125	4,554,000	2	EZCV250H4125	5,635,300	2
EZC250H	160	EZCV250H3160	4,647,500	2	EZCV250H4160	5,720,000	2
EZC250H	200	EZCV250H3200	5,080,900	2	EZCV250H4200	6,705,600	2
EZC250H	225	EZCV250H3225	5,080,900	2	EZCV250H4225	6,705,600	2
EZC250H	250	EZCV250H3250	5,080,900	2	EZCV250H4250	6,705,600	2

EasyPact EZC400-630 N/H

- Aplikasi untuk instalasi listrik dengan kapasitas pemutusan rendah.
- Kapasitas Pemutusan : 36 kA s/d 50 kA pada 380/415 VAC .
- Thermal magnetic trip unit, tidak dapat disetel (*non adjustable*).
- Fixed type, front connection.
- Satu ukuran (*frame size*) untuk semua rating.
- Memenuhi standar IEC 60947-2.



EZC400-630

EasyPact	Ir (A)	3P	Harga (Rp)	SS	4P	Harga (Rp)	SS
EasyPact EZC400N (36 kA)							
EZC400N	320	EZC400N3320N	3,148,200	1	EZC400N4320N	4,249,300	2
EZC400N	350	EZC400N3350N	3,273,600	1	EZC400N4350N	4,419,800	2
EZC400N	400	EZC400N3400N	3,405,600	1	EZC400N4000N	4,729,500	2
EasyPact EZC630N (36 kA)							
EZC630N	500	EZC630N3500N	5,397,500	2	EZC630N4500N	6,476,000	2
EZC630N	600	EZC630N3600N	5,938,000	2	EZC630N4600N	7,125,000	2
EasyPact EZC400H (50 kA)							
EZC400H	320	EZC400H3320N	3,714,700	2	EZC400H4320N	4,919,200	2
EZC400H	350	EZC400H3350N	3,790,600	2	EZC400H4350N	5,115,000	2
EZC400H	400	EZC400H3400N	3,941,300	1	EZC400H4000N	5,473,500	2
EasyPact EZC630H (50 kA)							
EZC630H	500	EZC630H3500N	6,086,500	2	EZC630H4500N	7,302,500	2
EZC630H	600	EZC630H3600N	6,694,500	2	EZC630H4600N	8,033,000	2

Smart-UPS On-Line SRT

5 kVA – 10 kVA technical specifications

Product feature	SRT5KRMXLW-HW	SRT5KXLI SRT5KRMXLI	SRT6KXLI SRT6KRMXLI	SRT8KXLI SRT8KRMXLI	SRT10KXLI SRT10KRMXLI
Output					
Power rating	5,000 VA/4,500 W		6,000 VA/6,000 W	8,000 VA/8,000 W	10,000 VA/10,000 W
Nominal output voltage	230 V (220 V, 240 V, 208 V user selectable)		230 V (220 V, 240 V user selectable)		
Output frequency	50/60 Hz ± 3 Hz (auto sense)		50/60 Hz ± 0.1 Hz (user selectable)		
Topology	Double-conversion online				
Online efficiency at full load (typical)	94%				
Green mode efficiency at full load (typical)	98%				
Output connections	Hardwire three-wire (1 PH + N + G) or (2 PH + G)	(6) IEC 320 C13 (4) IEC 320 C19	(6) IEC320 C13, (4) IEC320 C19, hardwire three-wire (1 PH + N + G)		
Input					
Nominal input voltage	208 V, 220 V, 230 V, 240 V	220 V, 230 V, 240 V		220 V/380 V, 230 V/400 V, 240 V/ 415 V	
Input voltage range full load (half load)	160 – 275 V (100 – 275 V)			160/277 – 275/476 V (100/173-275/476 V)	
Input frequency	40 – 70 Hz auto-selecting				
Input connection	Hardwire three-wire (1 Ph+N+G) or (2 PH + G)	Hardwire three-wire (1 Ph+N+G)		Hardwire three-wire (1 Ph+N+G), Hardwire five-wire (3 Ph+N+G)	
Batteries and runtime					
Battery type	Maintenance-free sealed lead-acid battery with suspended electrolyte, leak proof				
Typical backup time at 1/2 load (min.)	11.8 min.	8.7 min.	14.5 min.	11.5 min.	
Typical backup time at full load (min.)	4 min.	2.5 min.	5.2 min.	3.8 min.	
Replacement battery (quantity)	APCRBC140 (1)			APCRBC140 (2)	
External battery pack (tower/rack mount)	SRT192BP/SRT192RMBP			SRT192BP2/SRT192RMBP2	
Communication and management					
Interface ports	Embedded network management with environmental monitoring, which includes an RJ-45 with status LEDs (10/100 Base-T),				
Control panel	High-resolution graphical LCD display				
Emergency power off (EPO)	Yes (normally open, NO/ normally closed, NC connections)				
Physical					
Rack height	3 U	4 U	6 U	6 U	
Maximum height (RM)	130 mm	174 mm	263 mm	263 mm	
Maximum width (RM)	432 mm	432 mm	432 mm	432 mm	
Maximum depth (RM)	719 mm	719 mm	715 mm	715 mm	
Net weight	54.5 kg	60 kg	112 kg	112 kg	
Conformance					
Regulatory	UL-1778, FCC Part 15 Class A, CSA, CE, VDE, RCM, and EAC, IEC/EN 62040-1, IEC/EN 62040-2	CE, VDE, RCM, and EAC, IEC/EN 62040-1, IEC/EN 62040-2			
Warranty	Three years for electronics/two years for battery				